HSF

NOTES:
Current Rating:1AMP
Contact Resistance:20mΩ max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ min
Operation Temperature:−40℃ to +105℃

Contact Material:Brass
Contact plating:Au or Sn Over Ni
Insulator Material:PA6T+30%GF(UL94V−0)
6 To 8 Pin No "D" Configuration



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Ordering Information

3131- XX M XX B D 00 T X

No.of Pins	Contact Plating	Color Insulator	Packing
10 34	G0=Gold Flash	B=Black	T=Tube
14 40	G3=10u"Gold		
20 44	G4=15u"Gold		
24 50	SN=Tin		
26 60			
30 64			
32 80			
100			





With Post



Without Post

我司平整度为
0.15MM

Dimension antitheses list			
ITEM	C	W	H
Standard	6.60	5.50	1.50
Alternate			

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A5	2013/09/27	Modify	
A4	2013/01/14	ADD THE CAP	
A3	2011/12/27	Change The Part NO	——
A0	2008/04/25	NEW	——

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

DRAW	Tsingsn	DATE	2013/09/27
CHECK		DATE	
APPROVE		DATE	

SCALE	1:1
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

PART NO. 3131-XXMXXBD00TX

TITLE: 1.27 BOX HEADER SMT
H=5.70 ADD HOUSING

Customer NO.

WCON
Http: www.wcon-china.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon-china.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: wconks@wcon-china.com