


HSF




此处为结构示意图，以实际产品结构为准此图仅供参考

说明


1. 产品如图所示型態放入载带
2. 注意各标签样式、位置及方向的一致性；
3. 标签如客户有特殊要求，则按客户要求黏贴；
4. 打外箱包装带时需注意，打为十字型，另出国内客户，未打包装带。
5. 未尽事宜依据交货注意事项。

W	S	F	Reel/内箱	内箱/外箱
12.0±0.30	\	5.50±0.15	6	3
16.0±0.30	\	7.50±0.15	4	3
24.0±0.30	\	11.50±0.15	3	3
32.0±0.30	28.40±0.15	14.20±0.15	2	3
44.0±0.30	40.40±0.15	20.20±0.15	2	3
56.0±0.30	52.40±0.15	26.20±0.15	1	3
72.0±0.30	68.40±0.15	34.20±0.15	1	3
88.0±0.30	84.40±0.15	42.20±0.15	1	3
104.0±0.30	100.40±0.15	50.20±0.15	1	3




外箱：CTN-18K

No.4:
封箱, 打包, 贴标签。




No.1:

产品包装前, 注意载带要留空160mm以上
将产品放入载带凹槽后, 用盖带封装,
注意: 盖带与承载带的拉力30g-120g



No.3:

将内箱装入外箱 (3内箱/外箱)
注意统一标签方向



内箱：CTN-18E

No.2:

将卷盘套上防水袋,
放入1包干燥剂,
真空机封口后装入内箱,
用封箱胶封装好, 并贴上标签。

变更
记事

版次 REV	日期 DATE	变更说明 MODIFICATION DESCRIPTION	变更 CHANGE	核准 APPROVE
A0	2023/03/15	NEW	-----	-----

工程图 ENGINEERING	绘图 DRAW	苏珊	2023/03/15
X.X ±0.30	设计 DESIGN		
X.XX ±0.20	审核 CHECK		
X.XXX ±0.10	核准 APPROVE		
Angle ± 2'			
DIM TOL			

SCALE	FIT
UNIT mm	
SIZE A4	
SHEET 1/1	
PROJ.	

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

WCON
WCON ELECTRONICS (GUANGDONG) CO., LTD

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT

料号 PART NO.	品名 TITLE:
3524-382XXMXX060R1	1.27mm Machined Female Header, 2*XXP, 180° SMT